

Report 11382
22 February 1999

GENCORP
AEROJET

**Integrated Advanced Microwave Sounding Unit-A
(AMSU-A)**

Engineering Test Report

SARR, SARP, DCS Receivers, Link Frequencies

EMI Sensitive Band Test Results

AMSU-A2, S/N 106

**Contract No. NAS 5-32314
CDRL 207**

Submitted to:

**National Aeronautics and Space Administration
Goddard Space Flight Center
Greenbelt, Maryland 20771**

Submitted by:

**Aerojet
1100 West Hollyvale Street
Azusa, California 91702**

Aerojet

1962

**Report 11382
22 February 1999**

**Integrated Advanced Microwave Sounding Unit-A
(AMSU-A)**

Engineering Test Report

SARR, SARP, DCS Receivers, Link Frequencies

EMI Sensitive Band Test Results

AMSU-A2, S/N 106

**Contract No. NAS 5-32314
CDRL 207**

Submitted to:

**National Aeronautics and Space Administration
Goddard Space Flight Center
Greenbelt, Maryland 20771**

Submitted by:

**Aerojet
1100 West Hollyvale Street
Azusa, California 91702**



TABLE OF CONTENTS

Paragraph		Page
1	INTRODUCTION	1
1.1	General.....	1
1.2	Purpose	1
1.3	Scope	1
1.4	Summary of Test Results	1
2	TEST PROGRAM.....	2
2.1	Test Article	2
2.2	Test Starting and Completion Dates	2
2.3	Instrumentation	2
2.4	Test Frequencies	2
2.5	Operational Mode	4
2.6	Test Location	4
2.7	Test Procedure	4
2.8	Test Results.....	4
3	SUPPLEMENTARY INFORMATION	6
3.1	Supplementary Information	6

TABLE

Table		Page
I.	SARR, SARP, DCS Receiver, and Link Frequencies	3

FIGURES

Figure		Page
1	Test Data Sheet	7
2	Plot 1.....	10
3	Plot 2.....	11
4	Plot 3.....	12
5	Plot 4.....	13
6	Plot 5.....	14
7	Plot 6.....	15
8	Plot 7.....	16
9	Plot 8.....	17
10	Plot 9.....	18
11	Plot 10.....	19
12	Plot 11.....	20
13	Plot 12.....	21
14	Plot 13.....	22
15	Plot 14.....	23
16	Plot 15.....	24
17	Plot 16.....	25
18	Plot 17.....	26
19	Plot 18.....	27
20	Plot 19.....	28
21	Plot 20.....	29



Figures (Cont)

22	Plot 21.....	30
23	Plot 22.....	31
23	Plot 23.....	32
25	Plot 24.....	33
26	Plot 25.....	34
27	Plot 26.....	35
28	Plot 27.....	36
29	Plot 28.....	37
30	Plot 29.....	38
31	Plot 30.....	39
32	Plot 31.....	40
33	Plot 32.....	41
34	Plot 33.....	42
35	Plot 34.....	43
36	Plot 35.....	44
37	Plot 36.....	45
38	Plot 37.....	46
39	Plot 38.....	47
40	Plot 39.....	48
41	Plot 40.....	49
42	Plot 41.....	50
43	Plot 42.....	51
44	Plot 43.....	52
45	Plot 44.....	53
46	Plot 45.....	54
47	Plot 46.....	55
48	Plot 47.....	56
48	Plot 48.....	57
50	Plot 49.....	58
51	Plot 50.....	59
52	Plot 51.....	60
53	Plot 52.....	61
54	Plot 53.....	62
55	Plot 54.....	63



SECTION 1

INTRODUCTION

1.1 General

This document contains the procedures and test results of the discrete SARP EMI sensitive bands measurements performed on the AMSU-A2/METSAT instrument, part number 1331200-2, serial number 106. The test was performed as described in paragraph 3.4.6 of AE-26151/5D Test Procedure, Electromagnetic Interference (EMI)/Electromagnetic Radiation (EMR) and Electromagnetic Compatibility (EMC) for Advanced Microwave Sounding Unit-A (AMSU-A), dated 22 September 1998.

1.2 Purpose

The purpose of this report is to demonstrate that the frequency bands described in the Interface Specification, IS-3267415, paragraph 3.6.1.4.2 are not generated or present above the sensitivity level specified in the radiation requirements of the aforementioned specification.

1.3 Scope

This document describes the test performed by Aerojet, and it is presented in the following manner:

- | | |
|-----------|--|
| Section 1 | Contains general introductory material and a summary of the test results. |
| Section 2 | Contains a detailed description of the test plan, test procedure, and test results. |
| Section 3 | Contains supplementary test information, pertinent test data, and the list of test equipment used. |

1.4 Summary of Test Results

The test performed at each frequency band specified herein indicates that the AMSU-A2 instrument meets the requirements of the interface specification. No radiated emissions were detected in the measured frequency ranges above the sensitivity required.

SECTION 2

TEST PROGRAM

2.1 Test Article

The AMSU-A system passively monitors radiation from the earth's surface and atmosphere in the microwave portion of the spectrum. The instruments incorporate fifteen total-power super heterodyne type radiometers. The system is composed of two independent instruments. The module designated as AMSU-A2 contains the two lowest-frequency channels, i.e., Channel 1 has the 28.8 GHz frequency and Channel 2 has the 31.4 GHz frequency. The module designated as AMSU-A1 contains the thirteen remaining channels with frequencies from 50.8 GHz to 89 GHz.

Periodic on board calibration is accomplished by using an in-flight backbody calibration and cold space as energy reference sources. During each scan, the shrouded reflector observes 30 earth scene cells with one sample period each and two calibration target cells with two sample periods each. Complete end-to-end in-flight calibration from the antenna to the AMSU-A instrument output is provided for each channel. This will yield the maximum in-flight calibration accuracy that gives the radiometric data the required sensitivity and precision.

At each frequency, the half power antenna beamwidth is a constant 3.33°. Thirty contiguous scene resolution cells spaced 3.33° along the scan line are sampled in a stepped-scan fashion every eight seconds. The scan covers 50° on each side of the satellite path.

2.2 Test Starting and Completion Dates

The AMSU-A2 instrument, serial number 106, was tested between 24 November and 1 December 1998. No testing was performed during the period of 26 to 29 November 1998.

2.3 Instrumentation

All instrumentation was suitable for the purpose intended. Each instrument used was within its certification period. Instrumentation accuracy was verified by calibration in accordance with MIL-STD-45662 as implemented and controlled by Aerojet standard operating procedures. The attached Test Data Sheet 2, in Section 3, contains the list of the equipment with pertinent traceability information.

2.4 Test Frequencies

The test frequencies were selected from paragraph 3.6.1.4.2 of the interface specification, IS-3267415, as listed in Table I.

Table I. SARR, SARP, DCS Receiver, and Link Frequencies

Item No.	Frequency (MHz)		Level (dBm)	
1	118.0	–	120.0	-100
2	120.0	–	121.45	-125
3	121.45	–	121.485	-145
4	121.5 MHz ±15 kHz		-150	
5	121.515	–	121.550	-145
6	121.550	–	123.00	-125
7	123.00	–	125.00	-100
8	236.00	–	240.00	-100
9	240.00	–	242.925	-125
10	242.945	–	242.975	-145
11	243 MHz ±25 kHz		-150	
12	243.025	–	243.075	-145
13	243.075	–	246.00	-125
14	246.00	–	250.00	-100
15	385.10	–	401.10	-100
16	401.10	–	405.90	-125
17	405.90	–	406.00	-145
18	406.05 MHz ±50 kHz		-150	
19	406.10	–	406.20	-145
20	406.20	–	411.00	-125
21	411.00	–	425.00	-100
22	396.00	–	401.50	-125
23	401.50	–	401.60	-145
24	401.630 MHz ±50 kHz		-150	
25	401.700	–	401.800	-145
26	401.800	–	406.00	-120
27	2010	–	2040	-120

2.5 Operational Mode

The AMSU-A2 instrument was tested in the IN-ORBIT mode of operation. In this mode, the antenna is rotating continuously and all the circuits are working. The maximum electric field radiated emissions are produced in this mode of operation.

2.6 Test Location

This test was conducted in the shielded enclosure located in Building 183 of the Aerojet test facility.

2.7 Test Procedure

The test procedure used for the performance of this test was extracted from the Process Specification, Test Procedure. Electromagnetic Interference (EMI)/Electromagnetic Radiation (EMR) and Electromagnetic Compatibility (EMC) for Advanced Microwave Sounding Unit-A (AMSU-A), document number AE-26151/5D paragraph 3.4.6.3.1, steps 14 through 23 changed as described below:

Step 14 – Activate the HP70004 with the HP70620 amplifier. Program the analyzer for noise averaging to a minimum of eight times. Verify that the minimum discernable signal level is below the required dBm level indicated in the list for the frequency band indicated.

Step 15 – Connect the equipment of step 14 to the biconical antenna and measure the radiated levels throughout the frequency bands from 118.0 MHz to 125.0 MHz. Performed the test in both polarities of the antenna.

Step 16 - Connect the equipment to the Log Periodic antenna and measure the radiated levels throughout the frequency bands from 236.0 MHz to 406.0 MHz. Performed the test in both polarities of the antenna.

Step 17 - Connect the equipment to the double ridged warm antenna and measure the radiated levels throughout the frequency band from 2010 MHz to 2040 MHz. Perform the test in both polarities of the antenna.

Step 18 - All of the measurements performed in steps 15, 16, and 17 shall be below the signal sensitivity. No narrow band signals shall be above the limit whether ambient or generated by the equipment.

Step 19 - The measurement of steps 14 through 18 shall be at the equipment minimum discernable signal and detected narrow bands are below or at the sensitivity requirement levels in Table I.

2.8 Test Results

No radiated emissions were recorded above the specified sensitivity levels in Table I. The emissions detected were ambient emissions produced by the Halon System. Some emissions were introduced into the shielded enclosure via the interconnect cables. In this case, the cables were moved to an area of minimum emissions, i.e., until the detected emissions were below the specified level.

The first complete scan of all the required frequency bands was conducted during the 24th and 25th of November. A retest of the marginal frequency bands was conducted on the 30th of November and the 1st of December.

The recorded data is presented in this order:

- | | |
|--------------------|---|
| Plots 1 through 7 | Covers the frequency range from 118.00 MHz to 125.00 MHz, with the antenna in the horizontal position. |
| Plots 8 through 14 | Covers the above frequency range with the antenna in the vertical position. The detected emission that approximated the limit was a signal at 121.510 MHz, 2.07 dBm below the limit, with the antenna in the horizontal position. |

- | | |
|---------------------|---|
| Plots 15 through 21 | Covers the frequency range from 236.00 MHz to 250.00 MHz, with the antenna in the horizontal position. |
| Plots 22 through 28 | Covers the above frequency range with the antenna in the vertical position. The detected emission that approximated the limit was a signal at 242.983 MHz, 1.02 dBm below the limit, with the antenna in the horizontal position. |
| Plots 29 through 35 | Covers the frequency range from 385.10 MHz to 425.00 MHz, with the antenna in the horizontal position. |
| Plots 36 through 42 | Covers the above frequency range with the antenna in the vertical position. The detected emission that approximated the limit was a signal at 406.021 MHz, 0.72 dBm below the limit, with the antenna in the vertical position. |
| Plots 43 through 47 | Covers the frequency range from 396.00 MHz to 406.00 MHz, with the antenna in the horizontal position. |
| Plots 48 through 52 | Covers the above frequency range with the antenna in the vertical position. The detected emissions that approximated the limit was a signal at 401.601 MHz, 0.86 dBm below the limit with the antenna in the horizontal position. |
| Plots 53 and 54 | Covers the frequency range from 2,010 MHz and 2,040 MHz, with the antenna in the horizontal and vertical position respectively. All emissions are at a minimum 10 dBm below the limit. |

The referenced plots are presented in Section 3.

SECTION 3

SUPPLEMENTARY INFORMATION

3.1 Supplementary Information

This section contains the Test Data Sheet, Plots, and the equipment list.

AE-26151/5D
22 Sep 98

TEST DATA SHEET 2 (Sheet 1 of 3)
3.4.6: RE02 Test

Test Setup Verified: Ken Deane 11/21/98
Signature

3.4.6.3.1 Step 1: Test Equipment Log

Item	Manufacturer	Model/ Part No.	Aerojet Inventory No.	Calibration Date	Calibration Due Date
Spectrum Analyzer	HP	70004	C200064	11-12-98	11-12-99
with Amplifier	HP	70620	C200064	11-12-98	11-12-99
Plotter	HP	7475A XXXXX	47417	CNR	CNR
Biconical Antenna	HP	11955A	C200224	1-16-98	1-16-99
Log Periodic Antenna	HP	11956A	C200225	1-16-98	1-16-99
Horn Antenna	Electrometrics	RGA-10C	LSD8367	10-21-98	10-31-99

AE-26151/5D
22 Sep 98

TEST DATA SHEET 2 (Sheet 2 of 3)
3.4.6: RE02 Test (Cont)

Test Setup Verified: Ken Shultz 12-1-98
Signature

3.4.6.3.2: Emission Measurements

Step	Antenna/Frequency	Band	Required	Emissions within limits?		Comments/ Observations
				Yes	No	
4	All except Horn 14 kHz to 1 GHz	Narrow	See Figure 3			
6	All except Horn 14 kHz to 1 GHz	Broad	See Figure 4			12-1-98 <small>AMSL D SERIAL</small> N/R 91 30
12	Horn, RGA-100 1 to 2 GHz	Narrow	See Figure 3			
15	Biconical, EMCO 3104 121.5 MHz with Ampl	Narrow	No narrow- band freq. > -150 dBm	✓		
16	Log Conical, EMCO 3101 243 MHz, 401.65 MHz, & 406.05 MHz with Ampl	Narrow	No narrow- band freq. > -150 dBm	✓		
19	Horn, RGA-180 2010 to 2040 MHz with Ampl	Narrow	No narrow- band freq. > -120 dBm	✓		
21	Biconical/Log Conical 59.458 to 751.944 MHz	Narrow	No narrow- band freq. > -60 dBm			
21	400 to 500 MHz	Narrow	-107.1 dBm			
21	2 to 18 GHz	Narrow	Figure 3			
21	1217 to 1227 MHz	Narrow	-111.0 dBm	12-1-98 <small>AMSL D SERIAL</small>	N/R 91 30	
21	1565 to 1614 MHz	Narrow	-111.2 dBm			
21	2051.9 to 2055 MHz	Narrow	-126.7 dBm			
21	5254.7 to 5255.3 MHz	Narrow	-122.8 dBm			
21	5450 to 5825 MHz	Narrow	-80.7 dBm			

NOTE: Attach all backup data generated during the test (photos, printouts, plots, test logs, additional comments or observations, etc.) to this data sheet.

AE-26151/5D
22 Sep 98

TEST DATA SHEET 2 (Sheet 3 of 3)
3.4.6: RE02 Test (Cont)

Test Setup Verified: Ken Shaw 12-1-98
Signature

3.4.6.3.2: Emission Measurements

Step	Antenna*/Frequency Range (MHz)	Band	Radiation Limit (dBm)	Emissions within limits?		Comments/ Observations
				Yes	No	
22	118.000 - 120.000	Narrow	-100 / Table IV	✓	✓	
22	120.000 - 121.450	Narrow	-125 / Table IV	✓	✓	
22	121.450 - 121.485	Narrow	-145 / Table IV	✓	✓	
22	121.515 - 121.550	Narrow	-145 / Table IV	✓	✓	
22	121.550 - 123.000	Narrow	-125 / Table IV	✓	✓	
22	123.000 - 125.000	Narrow	-100 / Table IV	✓	✓	
23	236.000 - 240.000	Narrow	-100 / Table IV	✓	✓	
23	240.000 - 242.925	Narrow	-125 / Table IV	✓	✓	
23	242.925 - 242.975	Narrow	-145 / Table IV	✓	✓	
23	243.025 - 243.075	Narrow	-145 / Table IV	✓	✓	
23	243.075 - 246.000	Narrow	-125 / Table IV	✓	✓	
23	246.000 - 250.000	Narrow	-100 / Table IV	✓	✓	
23	385.100 - 401.100	Narrow	-100 / Table IV	✓	✓	
23	401.100 - 405.900	Narrow	-125 / Table IV	✓	✓	
23	405.900 - 406.000	Narrow	-145 / Table IV	✓	✓	
23	406.100 - 406.200	Narrow	-145 / Table IV	✓	✓	
23	406.200 - 411.00	Narrow	-125 / Table IV	✓	✓	
23	411.000 - 425.000	Narrow	-100 / Table IV	✓	✓	
23	396.000 - 401.500	Narrow	-125 / Table IV	✓	✓	
23	401.500 - 401.600	Narrow	-145 / Table IV	✓	✓	
23	401.700 - 401.800	Narrow	-145 / Table IV	✓	✓	
23	401.800 - 406.000	Narrow	-125 / Table IV	✓	✓	

- All frequency ranges are to be performed with antenna in both vertical and horizontal polarization.

Signature Date

1 Dec 98

Unit AMSU-A2 METSAT/METOP

Engineer: [Signature]

Serial No. 106

Quality Control: [Signature]

Shop Order 642843 Oper 0280000

Customer Representative: [Signature]

Figure 1. Test Data Sheet (Sheet 3 of 3)




Figure 2. Plot 1




Figure 3. Plot 2




Figure 4. Plot 3




Figure 5. Plot 4




Figure 6. Plot 5




Figure 7. Plot 6




Figure 8. Plot 7




Figure 9. Plot 8




Figure 10. Plot 9




Figure 11. Plot 10




Figure 12. Plot 11




Figure 13. Plot 12




Figure 14. Plot 13




Figure 15. Plot 14




Figure 16. Plot 15




Figure 17. Plot 16




Figure 18. Plot 17




Figure 19. Plot 18




Figure 20. Plot 19




Figure 21. Plot 20




Figure 22. Plot 21




Figure 23. Plot 22




Figure 24. Plot 23




Figure 25. Plot 24




Figure 26. Plot 25




Figure 27. Plot 26




Figure 28. Plot 27




Figure 29. Plot 28




Figure 30. Plot 29




Figure 31. Plot 30




Figure 32. Plot 31




Figure 33. Plot 32




Figure 34. Plot 33




Figure 35. Plot 34




Figure 36. Plot 35




Figure 37. Plot 36




Figure 38. Plot 37




Figure 39. Plot 38




Figure 40. Plot 39




Figure 41. Plot 40




Figure 42. Plot 41




Figure 43. Plot 42




Figure 44. Plot 43




Figure 45. Plot 44




Figure 46. Plot 45




Figure 47. Plot 46




Figure 48. Plot 47




Figure 49. Plot 48




Figure 50. Plot 49




Figure 51. Plot 59




Figure 52. Plot 51




Figure 53. Plot 52




Figure 54. Plot 53




Figure 55. Plot 54



FORMS



National Aeronautics and
Space Administration

Report Documentation Page

1. Report No. ---	2. Government Accession No. ---	3. Recipient's Catalog No. ---	
4. Title and Subtitle Integrated Advanced Microwave Sounding Unit-A (AMSU-A), Engineering Test Report		5. Report Date 22 February 1999	
		6. Performing Organization Code ---	
7. Author(s) A. Valdez		8. Performing Organization Report No 11382	
		10. Work Unit No. ---	
9. Performing Organization Name and Address Aerojet 1100 W. Hollyvale Azusa, CA 91702		11. Contract or Grant No. NAS 5-32314	
		13. Type of Report and Period Covered Final	
12. Sponsoring Agency Name and Address NASA Goddard Space Flight Center Greenbelt, Maryland 20771		14. Sponsoring Agency Code ---	
15. Supplementary Notes ---			
16. ABSTRACT (Maximum 200 words) This is the Engineering Test Report, SARR, SARP, DCS Receivers, Link Frequencies EMI Sensitive Band Test Results, AMSU-A2, S/N 107, for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A).			
17. Key Words (Suggested by Author(s)) EOS Microwave System		18. Distribution Statement Unclassified --- Unlimited	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of pages	22. Price ---

NASA FORM 1626 OCT 86

PREPARATION OF THE REPORT DOCUMENTATION PAGE

The last page of a report facing the third cover is the Report Documentation Page, RDP. Information presented on this page is used in announcing and cataloging reports as well as preparing the cover and title page. Thus, it is important that the information be correct. Instructions for filing in each block of the form are as follows:

Block 1. Report No. NASA report series number, if preassigned.

Block 2. Government Accession No. Leave blank.

Block 3. Recipient's Catalog No. Reserved for use by each report recipient.

Block 4. Title and Subtitle. Typed in caps and lower case with dash or period separating subtitle from title.

Block 5. Report Date. Approximate month and year the report will be published.

Block 6. Performing Organization Code. Leave blank.

Block 7. Authors. Provide full names exactly as they are to appear on the title page. If applicable, the word editor should follow a name.

Block 8. Performing Organization Report No. NASA installation report control number and, if desired, the non-NASA performing organization report control number.

Block 9. Performing Organization Name and Address. Provide affiliation (NASA program office, NASA installation, or contractor name) of authors.

Block 10. Work Unit No. Provide Research and Technology Objectives and Plants (RTOP) number.

Block 11. Contract or Grant No. Provide when applicable.

Block 12. Sponsoring Agency Name and Address. National Aeronautics and Space Administration, Washington, D.C. 20546-0001. If contractor report, add NASA installation or HQ program office.

Block 13. Type of Report and Period Covered. NASA formal report series; for Contractor Report also list type (interim, final) and period covered when applicable.

Block 14. Sponsoring Agency Code. Leave blank.

Block 15. Supplementary Notes. Information not included

elsewhere: affiliation of authors if additional space is required for Block 9, notice of work sponsored by another agency, monitor of contract, information about supplements (file, data tapes, etc.) meeting site and date for presented papers, journal to which an article has been submitted, note of a report made from a thesis, appendix by author other than shown in Block 7.

Block 16. Abstract. The abstract should be informative rather than descriptive and should state the objectives of the investigation, the methods employed (e.g., simulation, experiment, or remote sensing), the results obtained, and the conclusions reached.

Block 17. Key Words. Identifying words or phrases to be used in cataloging the report.

Block 18. Distribution Statement. Indicate whether report is available to public or not. If not to be controlled, use "Unclassified-Unlimited." If controlled availability is required, list the category approved on the Document Availability Authorization Form (see NHB 2200.2, Form FF427). Also specify subject category (see "Table of Contents" in a current issue of STAR) in which report is to be distributed.

Block 19. Security Classification (of the report). Self-explanatory.

Block 20. Security Classification (of this page). Self-explanatory.

Block 21. No. of Pages. Count front matter pages beginning with iii, text pages including internal blank pages, and the RDP, but not the title page or the back of the title page.

Block 22. Price Code. If Block 18 shows "Unclassified-Unlimited," provide the NTIS price code (see "NTIS Price Schedules" in a current issue of STAR) and at the bottom of the form add either "For sale by the National Technical Information Service, Springfield, VA 22161-2171" or "For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402-0001," whichever is appropriate.

DOCUMENT APPROVAL SHEET



TITLE			DOCUMENT NO.	
<u>Engineering Test Report</u> SARR, SARP, DCS Receivers, Link Frequencies EMI Sensitive Bank Test Results, AMSU-A2, S/N 106			Report 11382 22 February 1999	
INPUT FROM: A. Valdez	CDRL: 207	SPECIFICATION ENGINEER: J. Kirk	DATE	
CHECKED BY: N/A	DATE	JOB NUMBER: N/A	DATE	
APPROVED SIGNATURES			DEPT. NO.	DATE
Product Team Leader (L. Paliwoda) <u>L. Paliwoda</u> Systems Engineer (R. Platt) <u>R. Platt</u> Design Assurance (E. Lorenz) <u>E. Lorenz</u> Quality Assurance (R. Taylor) <u>R. Taylor</u> <u>for</u> Technical/PMO (P. Patel) <u>P. K. Patel</u> Released: Configuration Management (J. Cavanaugh) <u>J. Cavanaugh</u>			7888 8341 8331 7831 8341 8361	3-4-99 3/15/99 3/9/99 3/12/99 3/14/99 3/15/99
By my signature, I certify the above document has been reviewed by me and concurs with the technical requirements related to my area of responsibility.				
(Data Center) <u>FINAL</u>				
Please return this sheet and the reproducible master to Jim Kirk (Bldg. 1/Dept. 8631), ext. 2081.				



REPORT DOCUMENTATION PAGE

*Form Approved
OMB No. 0704-0188*

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)			2. REPORT DATE February 1999		3. REPORT TYPE AND DATES COVERED Contractor Report		
4. TITLE AND SUBTITLE Integrated Advanced Microwave Sounding Unit-A (AMSU-A) Engineering Test Report			5. FUNDING NUMBERS NAS5-32314				
6. AUTHOR(S) A. Valdez							
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS (ES) Aerojet 1100 W. Hollyvale Azusa, CA 91702			8. PERFORMING ORGANIZATION REPORT NUMBER 11382 February 1999				
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS (ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING / MONITORING AGENCY REPORT NUMBER NASA/CR-1999-209502				
11. SUPPLEMENTARY NOTES							
12a. DISTRIBUTION / AVAILABILITY STATEMENT Unclassified–Unlimited Subject Category:19 Report available from the NASA Center for AeroSpace Information, 7121 Standard Drive, Hanover, MD 21076-1320. (301) 621-0390.				12b. DISTRIBUTION CODE			
13. ABSTRACT (Maximum 200 words) This is the Engineering Test Report,SARR, SARP, DCS Receivers, Link Frequencies EMI Sensitive Band Test Results AMSU-A2, S/N 106, for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A).							
14. SUBJECT TERMS EOS, Microwave System					15. NUMBER OF PAGES 63		
					16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT Unclassified		18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified		19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified		20. LIMITATION OF ABSTRACT UL	

